

# ABAQA 5-mil Textured Floor Laminate



**ABAQA 5-mil Textured Floor Laminate** is a 5.0-mil, clear, textured overlamine film with a velvet/matte finish. This calendered vinyl overlamine film should be considered as an inexpensive alternative to polycarbonate laminate. It has a permanent acrylic pressure-sensitive adhesive formulated for exceptional clarity. This product is supplied on a 1.5 mil polyester clear liner designed to provide an extremely smooth adhesive coating and is certified slip- and flame-resistant.

Benefits	Applications	Customers
<ul style="list-style-type: none"><li>Designed for easy installation, repositioning and removal without wrinkling or tearing</li><li>Slip-resistant for floor graphics</li><li>Excellent stability</li><li>Classified under UL 410 for floor graphics overlay applications</li><li>Class A, ASTM E84 flame resistance</li><li>Ability to contour cut and apply without stretching</li></ul>	<ul style="list-style-type: none"><li>Overlay for temporary floor signs</li><li>Overlay for Decals</li><li>Overlay for Counter mats</li><li>Overlay for Mouse pads</li><li>Overlay for Point-of-purchase floor graphics on commercial carpets</li></ul>	<ul style="list-style-type: none"><li>Print Service Providers</li><li>Graphic Artists</li><li>Sign Shops</li><li>Retail</li></ul>

SPECIFICATIONS	
Material Type	Scratch-resistant overlaminate film
Gauge	150 microns
Weight without Liner	410 gsm
Opacity	98%
Core Size	3-in
Finishing	Matte
Optimal Service Environment	Service temperature -40°F to +200°F
Ideal Storage Conditions	One-year shelf life when stored at 21Â°C and 50% relative humidity
Color	White
Ink Compatibility	Solvent and UV curable inks
Adhesion	To stainless steel 40 oz/in. Tested according to PSTC-101 Method A with 24-hour dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary. Test thoroughly before production.
Shelf Life	One-year shelf life when stored at 70°F and 50% relative humidity
Flame Resistance	ASTM E84 Class 1 or A Rating
Liner	Lay-flat liner
Liner Thickness	135gsm
Adhesive Thickness	25 microns
Temperature Range	Minimum application temperature +40°F. Service temperature range -40°F to +200°F.
Dimensional Stability	Good
Water Resistance	Limited immersion resistance. Test for specific applications.
Humidity Resistance	Good
Slip Resistance	UL 410 for floor graphics overlay applications

SKU	Size
5MTFL54	54-in x 100-ft

**Product Performance & Suitability:** All of the descriptive information and recommendations should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind. All purchasers shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential (Including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.