

ABAQA Embossed Indoor Floor & Wall Vinyl



The ABAQA Embossed Indoor Floor & Wall Vinyl is a matte, semi-rigid calendared vinyl with a pressure-sensitive adhesive that is specially formulated with a high-tack removable glue backed by a 135gsm lay-flat liner. This special combination of vinyl and adhesive allows the removability of this product from normal wall surfaces. Designed for wall murals, decals and graphics, the ABAQA Embossed Indoor Floor & Wall Vinyl sticks to most flat, semi-gloss, and gloss painted surfaces. The 135gsm tight-release liner provides excellent stability when printed with standard latex, solvent and UV curable inks. ***The material has an R10B slip-certification for safe use on floor graphics.***

Benefits	Applications	Customers
Designed for easy installation, repositioning and removal without wrinkling or tearing <ul style="list-style-type: none">Slip-resistant for floor graphicsExcellent stabilityMatte finish for vivid graphicsClass A, ASTM E84 flame resistanceAbility to contour cut and apply without stretching	Wall Murals <ul style="list-style-type: none">Wall Cut-outsDecalsIndoor and Short-termOutdoor SignagePoint-of-sale DisplaysTrade Show Graphics	Print Service Providers <ul style="list-style-type: none">Graphic ArtistsSign ShopsRetail

SPECIFICATIONS	
Material Type	Adhesive-backed embossed canvas semi-rigid calendared vinyl film
Gauge	150 microns
Weight without Liner	410 gsm
Opacity	98%
Core Size	3-in
Finishing	Matte
Optimal Service Environment	Service temperature -40°C to +93°C
Ideal Storage Conditions	One-year shelf life when stored at 21°C and 50% relative humidity
Color	White
Ink Compatibility	Latex, Solvent and UV curable inks
Adhesion	To glass 18 N/25mm (FTM01) To standard test panels 10 N/25mm (FTM01) Individual values may vary. Bond to wall surfaces may vary. Test thoroughly before production.
Shelf Life	One-year shelf life when stored at 21°C and 50% relative humidity.
Flame Resistance	ASTM E84 Class 1 or A Rating
Liner	Layflat liner
Liner Thickness	135gsm
Adhesive Thickness	25 microns
Temperature Range	Minimum application temperature +4,4°C. Service temperature -40°C to +93°C.
Dimensional Stability	Good
Removability	Removable up to 1 year under normal interior conditions.
Water Resistance	Limited immersion resistance. Test for specific applications.
Humidity Resistance	Good
Slip Resistance	R10 B certification for barefoot and wet areas
SKU	Size
EIFWV54	54-in x 100-ft

Product Performance & Suitability: All of the descriptive information and recommendations should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind. All purchasers shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential (Including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.